



PowerFirst Technology Company Limited

深圳市顶尖电源科技有限公司

Address: Lantian Bld., Kaitian Science Park, Pinghu Street, Shenzhen, China.

地址: 深圳市龙岗区平湖街道平安大道108号开田科学园蓝田大厦

Tel: +86 755 28441619 / Email: marketing@epowerfirst.com Web: www.epowerfirst.com

Technical Specification for PFC0300 (Confidential)

CONTENTS:

1 INTRODUCTION 1

2 DOCUMENT HISTORY 1


3 SPECIFICATION..... 1-3

4 PRODUCT OUTLINE DRAWING 3

5 CHARGING ALGORITHMS 4


1 INTRODUCTION

This document specifies the requirements for PFC0300 series, it is a fan-cooling model. Dip-switches are used to select the commonly-used charging algorithms, the default setting is marked with “■”.

1#  IU1a-Acd for Wet traction batteries

2#  IU1a-GEL for Gel or AGM

3#  IUUa-GEL for Gel or AGM

4#  For customized algorithm

Below product pictures are for reference only, it is based on the standard specification sheet, physical product might have minor change subject to customer’s specific request.



2 DOCUMENT HISTORY

Table 2-1 Document History

Version	Date	Change record	Creator
V.01	10.05.10	Initial version	PowerFirst

3 SPECIFICATION

Table 3-1 Specification

No	Item	Technical specification	Remark
1	Rated input voltage	100 -240 VAC +/-10%, stepless change	Universal wide range
2	AC frequency	50-60Hz	Universal
3	Peak efficiency	91% @230VAC/24VDC, 89% @120VAC/24VDC	
4	Power factor	>0.98 @ 230VAC, >0.99 @ 120VAC	Advanced Active PFC









PowerFirst Technology Company Limited

深圳市顶尖电源科技有限公司

Address: Lantian Bld., Kaitian Science Park, Pinghu Street, Shenzhen, China.

地址: 深圳市龙岗区平湖街道平安大道108号开田科学园蓝田大厦

Tel: +86 755 28441619 / Email: marketing@epowerfirst.com Web: www.epowerfirst.com**Technical Specification for PFC0300 (Confidential)**

No	Item	Technical specification	Remark
5	Nominal output voltage	24V	24V / 36V / 48V models optional
6	Bulk charge (CC)	10A, switch to CV @ 28.8V (2.40vpc)	Constant Current
7	Absorption charge (CV)	Hold at 28.8V (2.40vpc at battery end), switch to float charge when current tapers down to 0.5~0.8A	Constant Voltage
8	Float charge	27V (2.25vpc), no time limit	Constant Voltage
9	Interlock function	Normally-closed (NC), max. 5A Wires: 2 * 1mm ² * 20cm, Red and Black Connector: customizable	Optional, customizable
10	Remote LED extension	Connector customizable	Optional, customizable
11	Charge algorithms	<p>1#  IU1a-Acd for Wet traction batteries</p> <p>2#  IU1a-GEL for Gel or AGM</p> <p>3#  IUUa-GEL for Gel or AGM (default)</p> <p>4#  For customized algorithm</p>	<p>Take out the cap on the housing, set charging profile by the dip-switches</p> 
12	Line loss compensation	Based on 2 meters output cable's length	
13	Short circuit protection	Short circuit protection with auto-reset	
14	Reverse polarity protection	Reverse polarity protection with auto-reset	
15	Additional protection	Sparks protection AC surge protection with auto-reset Over temperature protection with auto-reset	
16	DC output power cord (customizable)	Cable: 2 * 2.5mm ² * 1000mm Connector: customizable	
17	AC input power cord (customizable)	Cable: 3 * 0.75mm ² * 600mm Connector: IEC320 / C14	
18	LED instruction	Red: On = Fault Yellow: On=Charging Green: On=Fully charged	Customizable
19	Regulatory compliant	Safety (LVD): EN60335-2-29, UL1564, CSA 107.2 Emissions (EMC): EN55014 Immunity (EMC): EN61000-3-2, EN61000-3-3	LVD, RE, CE, Harmonic, Flicker, ESD, RS, CS, EFT, Surge, DIP, PFM included



PowerFirst Technology Company Limited

深圳市顶尖电源科技有限公司


Address: Lantian Bld., Kaitian Science Park, Pinghu Street, Shenzhen, China.

地址: 深圳市龙岗区平湖街道平安大道108号开田科学园蓝田大厦


Tel: +86 755 28441619 / Email: marketing@epowerfirst.com Web: www.epowerfirst.com


Technical Specification for PFC0300 (Confidential)

2#  IUla-GEL for Gel or AGM



3#  IUUa-GEL for Gel or AGM



4#  For customized algorithm